

AIPHONE® WIRE BY STOCK NUMBER

STOCK #	LENGTH	AWG	DESCRIPTION	INSULATION	CAPACITANCE	LOOP RES.
81221650C	500'	22	16 conductor, non-shielded	PVC	23.60 pf/ft	17.50 ohm
82180210C	1000'	18	2 conductor, overall shield	PVC	47.00 pf/ft	6.92 ohm
82180310C	1000'	18	3 conductor, overall shield	PVC	47.00 pf/ft	6.92 ohm
82220250C	500'	22	2 conductor, overall shield	PVC	44.65 pf/ft	17.50 ohm
82220210C	1000'	22	2 conductor, overall shield	PVC	44.65 pf/ft	17.50 ohm
82220350C	500'	22	3 conductor, overall shield	PVC	44.62 pf/ft	17.50 ohm
82220650C	500'	22	6 conductor, overall shield	PVC	44.65 pf/ft	17.50 ohm
82221050C	500'	22	10 conductor, overall shield	PVC	44.65 pf/ft	17.50 ohm
82221250C	500'	22	12 conductor, overall shield	PVC	44.65 pf/ft	17.50 ohm
82221550C	500'	22	15 conductor, overall shield	PVC	44.65 pf/ft	17.50 ohm
82222050C	500'	22	20 conductor, overall shield	PVC	44.65 pf/ft	17.50 ohm
85160210C	1000'	16	2 conductor, low cap, PE, solid, non-shielded	PE	12.50 pf/ft	4.02 ohm
851602DB10C	1000'	16	2 conductor, low cap, PE, solid, non-shielded, direct burial	PE	12.50 pf/ft	4.16 ohm
85220710C	1000'	22	7 conductor, low cap, PE, non-shielded	PE	16.50 pf/ft	17.50 ohm
86220810C	1000'	22	4 twisted pair, low cap, PE, overall shield	PE	15.28 pf/ft	10.15 ohm
86221025C	250'	22	5 twisted pair, low cap, PE, overall shield	PE	15.28 pf/ft	10.15 ohm
87180250C	500'	18	2 conductor, low cap, PE, solid, non-shielded	PE	11.05 pf/ft	6.39 ohm
87180210C	1000'	18	2 conductor, low cap, PE, solid, non-shielded	PE	11.05 pf/ft	6.39 ohm
871802P10C	1000'	18	2 conductor, low cap, PVC, solid, non-shielded, plenum rated	FEP	13.00 pf/ft	6.52 ohm
87180450C	500'	18	4 conductor, low cap, PE, solid, non-shielded	PE	13.60 pf/ft	6.39 ohm
871804P50C	500'	18	4 conductor, low cap, PE, solid, non-shielded, plenum rated	FEP	23.60 pf/ft	6.80 ohm
87200250C	500'	20	2 conductor, mid cap, PE, solid, non-shielded	PE	20.96 pf/ft	10.15 ohm
87200210C	1000'	20	2 conductor, mid cap, PE, solid, non-shielded	PE	20.96 pf/ft	10.15 ohm
872002P10C	1000'	20	2 conductor, mid cap, PE, solid, non-shielded, plenum rated	FEP	18 pf/ft	10.15 ohm

WIRE NUMBER CODING

1st digit: 8 = Aiphone approved wire

2nd digit: Type of wire → 1 = non-shielded 5 = low capacitance
 2 = shielded 6 = twisted pair / shielded
 3 = twisted pair 7 = solid PE, low / mid capacitance

3rd & 4th digits: Gauge → 22 = 22 AWG 20 = 20 AWG 18 = 18 AWG 16 = 16 AWG

5th & 6th digits: Number of conductors → 02 = 2-conductors 12 = 12-conductors

7th & 8th digits: Length of wire → 10 = 1,000' box 50 = 500' box 25 = 250' box

9th digit: "C" indicates new wire

DB = Direct Burial

P = Plenum

WIRE NUMBER CODING EXAMPLE

1st: Aiphone Approved **2nd:** TYPE - Shielded **3rd & 4th:** GAUGE - 22 AWG **5th & 6th:** CONDUCTORS 02=2 Conductors **7th & 8th:** WIRE LENGTH 10=1,000' Box **9th:** "C" is New Wire

8

2

22

02

10

C

WIRE INFORMATION

All wire is stranded unless otherwise indicated.

Non-plenum wires have a gray jacket. Plenum wires have a natural jacket.

All wire meets the following standards: UL, C(UL), UL 444, CA Fire Marshal

Contact Aiphone for current pricing.

Using Aiphone wire extends your product warranty by one year.